HASSELBLAD

User Manual

H4D-200MS

H4D-60

H4D-50MS

H4D-50

H4D-40

H4D-31

1

2

Camera

The **Camera** setting automatically corresponds to an H4D body in normal use. However, when the sensor unit is attached to a large format/view camera then other settings must be manually made. See separate section for further information.

About

Hasselblad regularly releases updates to the firmware of the sensor unit. These updates not only improve the efficiency but also often add new features. The About box will tell you which firmware version is present so you can see if you have the latest (which can be downloaded from the Hasselblad website). The serial number is also displayed in case Hasselblad Support need to know it for any eventual problem solving.

The About box also shows the focus calibration ID (which must match the information on the grip display under 'System Status' to obtain the optimum performance). Each sensor unit is carefully adjusted to match the corresponding camera body, which in turn produces the matching verifications respectively. If you want to use different sensor units with different camera bodies, please refer to a Hasselblad Service Center for more information.

To obtain the About information:

1. *Select* **MAIN MENU > SETTINGS > ABOUT**.
2. *Press ➤ to open the* ***About*** *dialog, which shows the serial number and firmware version. When you are done reading the information, press the menu (***EXIT***) button to return to the* **SETTINGS** *menu. Either move on to another setting by using the navigator button or press the menu (***EXIT***) button again to exit the menu system.*

Default

The **DEFAULT** setting will reset all custom settings you have made back to the original default / factory settings.

To reset all settings:

1. *Select* **MAIN MENU > SETTINGS > DEFAULT**.
2. *Press the* **OK** *button and then the* **EXIT** *to return.*

1

2

Hasselblad A/S
Hejrevej 30, DK - 2400 Copenhagen,
Denmark

Victor Hasselblad AB
Box 220, SE - 401 23 Göteborg,
Sweden

09.2011 - UK v15